



APPLED ELECTRONICS ENTERPRISES CORPORATION

TEL: (02) 2545881 / 6224308 FAX: (02) 2545881 MOBILE: (0917) 8878378 / (0922) 8878374

STALL NO. 2M-15 168 MALL SOLER ST., BINONDO, MANILA, PHILIPPINES 1006

URL: WWW.LED.PH

EMAIL: APPLED888@YAHOO.COM.PH

PH7.62mm Indoor/Semi-outdoor LED display

Features

1. Multi-color, single color models available
2. 24 display modes, 5 display speeds, 10 stop-time
3. Adjustable font size and style, 15 fonts from very small to very large type
4. 28 attached icons of alterable color, international character of changeable font
5. Single color: 2 kinds of text colors, 2 colors image display
6. Multi-color: 12 kinds of text colors, 8 colors image display
7. High precision real time clock & calendar, 10 kinds of time formats
8. All characters, numbers, and symbols are available
9. All texts flush modes, default flush left
10. Temperature function available Fahrenheit /Celsius display mode optional (Temperature sensor is required)
11. 512K internal message storage memory; Long durability of 10 years or longer
12. Total 36 messages available. Each message can be mixture of text/graphic/time/temperature. Every message supports 2K of text and 8K of graphics
13. Addressable display operation available- control multiple displays in one network
14. Automatic power on/off by time of day and/or day-of-the-week optional
15. Automatic message switching by time of day and/or day-of-the-week optional
16. 8 grades of brightness adjustment manually; user-defined brightness grade in 4 time periods
17. PC software integrates all kinds of communications, switch RS-232 standard optional
18. RS-485, Ethernet ,Wireless RF, GSM available
19. Firmware and fonts update on-line



APPLED ELECTRONICS ENTERPRISES CORPORATION

TEL: (02) 2545881 / 6224308 FAX: (02) 2545881 MOBILE: (0917) 8878378 / (0922) 8878374

STALL NO. 2M-15 168 MALL SOLER ST., BINONDO, MANILA, PHILIPPINES 1006

URL: WWW.LED.PH

EMAIL: APPLED888@YAHOO.COM.PH

Specifications:

Pixel pitch	7.62mm
Character height	38mm, 53mm, 76mm, 114mm, 175mm, 236mm
LED size	5mm diameter
LED module	5x7 pixels(single line sign); 8x8 pixels
Pixel configuration	Monochrome: 1LED/pixel; Tricolor: 1R1G/pixel
LED density	17222pixels/M2
Brightness	Indoor>700CD/M2; Semi-outdoor>2500CD/M2
Viewing Angle	110/40 Degree
Best Viewing Distance	Indoor:1-20M; Semi-outdoor: 1-30M
IP Rate	31
Input Voltage	110/220V(AC)
Working environment temp	-30 °C ~+65 °C
Working environment humidity	10%~95%RH
System operating platform	Windows 2000/ XP/Vista
Communication(default)	RS232
Production time	18-25days
Warranty	1 year
Software	LED moving sign 2007



APPLED ELECTRONICS ENTERPRISES CORPORATION

TEL: (02) 2545881 / 6224308 FAX: (02) 2545881 MOBILE: (0917) 8878378 / (0922) 8878374

STALL NO. 2M-15 168 MALL SOLER ST., BINONDO, MANILA, PHILIPPINES 1006

URL: WWW.LED.PH

EMAIL: APPLED888@YAHOO.COM.PH

PH7.62mm Indoor (normal bright) LED display(Red, Tricolor)



PH7.62mm
Semi-outdoor
(Ultra bright)
LED display
(Red,
Green,
Blue,
Yellow,
White)