



APPLED ELECTRONICS ENTERPRISES CORPORATION

TEL: (02) 2545881 / 6224308 FAX: (02) 2545881 MOBILE: (0917) 8878378 / (0922) 8878374

STALL NO. 2M-15 168 MALL STA. ELENA ST., BINONDO, MANILA

URL: WWW.LED.PH

EMAIL: APPLED888@YAHOO.COM.PH

LED Tube Light

Specification

Part No: APP-T8A-150CM-T23W





APPLIED ELECTRONICS ENTERPRISES CORPORATION

TEL: (02) 2545881 / 6224308 FAX: (02) 2545881 MOBILE: (0917) 8878378 / (0922) 8878374

STALL NO. 2M-15 168 MALL STA. ELENA ST., BINONDO, MANILA

URL: WWW.LED.PH

EMAIL: APPLED888@YAHOO.COM.PH

Introduction

LED tubes are the ideal replacement for the conventional fluorescent tube, energy-saving up to 70%. Designed with advanced heat dissipation technology, used high brightness SMD LED and super internal constant current driver, Low-Carbon LED tubes are brighter than conventional fluorescent tube, better than most similar LED tubes in the market.

Product Features

- High Brightness: Taiwan Epistar chip, light efficiency of tube reach to 100lm/w;
- Super driver: Conversion efficiency above 93% and power factor reach to 98%;
- Thermal technology: Advanced technology with first class radiator materials;
- Modular Structure: Modular design, easy assembly and disassembly.
- Certificate: CE, FCC, PSE, C Tick approval and RoHS compliant;
- Warranty: 3 years.

Technical Specification

	Part No.	APP-T8A-150CM-T23W
	Rated Power	23W
	Input Voltage	AC85V-265V,50-60Hz
	LED Quantity	336PCS
	Color Temperature	2800k~3200K;4000k~4500K;5500k~6500K
	Conversion Efficiency	93%
	Power Factor	0.98
	Beam Angle	120°
	Pin Type	G13
	Dimension	φ 30*L1498mm
Product photo (SMD 3528)	Diffuser	Transparent PC
Luminous Flux	2350lm±100lm	
Illuminance	1m=530lux,2m=195lux,3m=98lux	
Operate Temperature	-20°C~+50°C	
Storage Temperature	-20°C~+50°C	
Color Rendering Index	>70	
Materials	Aluminum alloy&PC	
Equal to conventional fluorescent tube	58W+8W (Ballast Power)	





APPLIED ELECTRONICS ENTERPRISES CORPORATION


TEL: (02) 2545881 / 6224308 FAX: (02) 2545881 MOBILE: (0917) 8878378 / (0922) 8878374

STALL NO. 2M-15 168 MALL STA. ELENA ST., BINONDO, MANILA


URL: WWW.LED.PH

EMAIL: APPLIED888@YAHOO.COM.PH


Illuminance



Viewing Angle



Dimension Drawing



Application

Ideal replacement for conventional fluorescent tubes, widely used for office, factory, parking lot, residential, warehouse, signage, passenger interiors, supermarket, shop, vehicle interiors, etc



APPLIED ELECTRONICS ENTERPRISES CORPORATION

TEL: (02) 2545881 / 6224308 FAX: (02) 2545881 MOBILE: (0917) 8878378 / (0922) 8878374


STALL NO. 2M-15 168 MALL STA. ELENA ST., BINONDO, MANILA

URL: WWW.LED.PH

EMAIL: APPLED888@YAHOO.COM.PH

Installation

To avoid the danger of being shocked or electrocuted, turn off power to the fixture and unplug or detach fixture from source of power.



Package

Outer Carton: 1550*225*185mm(20pcs/box)

Net weight per tube: 510g

Gross weight per tube: 736g

Gross weight: 15.9kg/Carton

